

[Home](#) ■ [Products](#) ■ [Grit Separation and Treatment](#) ■ [Longitudinal Grit Traps](#)

## Longitudinal Grit Traps

For the reason of operating reliability of wastewater treatment plants it is necessary to separate the grit transported with the wastewater and other mineral materials (approx. 60 l / 1000 m<sup>3</sup> of wastewater) from the digestible organic material.

Due to the significant organics content in the classified grit longitudinal grit traps are today additionally aerated to at least partly avoid settling of organic material in the grit trap and cause floating material (grease) to rise to the surface. According to Kalbskopf, aerated grit traps are generally laid out on the basis of the residence time of wastewater in the grit trap. However, even aerated grit traps are unable to ensure reliable separation of grit from organics. This can only be achieved by well performing grit washing plants.

- [HUBER Longitudinal Grit Trap ROTAMAT® Ro6](#)
- [HUBER Grit Trap GritWolf®](#)

## Downloads

 [Brochure: HUBER Longitudinal Grit Trap ROTAMAT® Ro6](#) [pdf, 192 KB]  
Further information

 [Brochure: HUBER Grit Trap GritWolf®](#) [pdf, 205 KB]  
Further information

## Case Studies

- [New HUBER Grit Trap GritWolf® setting new standards: Grit removal below 100 µm](#)

**HYDROFLUX**  
WATER | SCIENCE | TECHNOLOGY**Hydroflux Pty Ltd**  
Level 26, 44 Market St  
Sydney NSW 2000  
AustraliaPhone +61 2 9089 8833  
Fax +61 2 9089 8830  
Email [info@hydroflux.com.au](mailto:info@hydroflux.com.au)  
WWW [www.huber-technology.net.au](http://www.huber-technology.net.au)Representative of the HUBER group:  
[www.huber.de](http://www.huber.de)