

[Home](#) ■ [Products](#) ■ [Safe Access Solutions](#) ■ [Technical Doors](#) ■ [Chlorine Room Door](#)

## Single/Double Chlorine Room Door TT5



### Access door for buildings in potable water supply where chlorine gas is stored or used

Chlorine room door, ready for installation, double skinned, completely made from 1.4404 (AISI 316 L) stainless steel, with double rubber seal.

The door and frame closing flush, the door opening to the outside (in escape direction), in accordance with UVV and DVGW standards.

Optional surface finish (lacquer with or without anti-graffiti properties, copper covering, wooden panelling).

### Download Documents

Here you will find extensive planning documents and customer information.

For quick and easy download, all documents of the product are packed together into one complete ZIP file:

- [Single/Double Chlorine Room Door TT5](#)

### More products of this group: Technical Doors

- [Stainless Steel Doors](#)

- [Safety Door](#)
- [Flood-proof Door](#)
- [Pressure-tight Door](#)
- [Access/Inspection Cover](#)
- [Louvre](#)
- [Windows](#)



**Hydroflux Pty Ltd**  
Level 26, 44 Market St  
Sydney NSW 2000  
Australia

Phone +61 2 9089 8833  
Fax +61 2 9089 8830  
Email [info@hydroflux.com.au](mailto:info@hydroflux.com.au)  
WWW [www.huber-technology.net.au](http://www.huber-technology.net.au)

Representative of the HUBER group:  
[www.huber.de](http://www.huber.de)

---